



POWERFUL MODULAR RELIABLE DURABLE ROBUST 60 % increased lifting capacity in single fall operation

Powerful motor with low operating temperature and cooling

Profile steel chain hardened, with increased service life

Robust housing and cover made of aluminum die casting

Protection class IP65 as standard, and many more options available

Polygonal connections for quick assembly and disassembly






SWISSNESS Swiss Design Made in Switzerland Since 1957

www.gis-ag.ch

OUTSTANDING FEATURES LIFTING CAPACITY 80 - 1250 KG

- 1 Powerful built-in motor (60 °C in ISO M5/FEM 2m)
- 2 Casing and cover made of aluminum, modular and simple in its design
- 3 Reliable DC spring-loaded brake, safe holding of the load
- Dry running slipping clutch, 4 very low maintenance
- 5 Eyebolt suspension hinged, easy installation





Motor

- Powerful built-in motor with power reserve
- Optimal cooling effect
- thanks to external cooling
- 3- or 1-phase operation



Transmission

- Smooth running (65 dB)
- 3-step gear with helical gearing
- 11 Permanent lubrication
- Self-contained gearbox .



Geared limit switch

- The upper and lower end . position of the load hook can be set easily and precisely
- Optionally two additional emergency stop contacts available



Protection class IP65

Dust proof

Control switch

Safe to operate

control cable

.

- Protected against water jets
- Best suited for outdoor operation 11 and dusty environment

Ergonomic and impact-resistant

External strain relief protects

42 V low voltage control





Profile steel chain

- Case hardened and manganese phosphated
- Less wear, increased lifetime Chain safety factor min. 8:1 .
- (ISO M5/FEM 2m)
- Corrosion resistance

Hooks

- Skeleton load and suspension hooks
- Hook safety catch fastened into position when closed

Polygonal connections

- All shaft-hub connections are built in a self-centering polygonal design
- Optimal power transmission
- Quick assembly and disassembly

Maintenance

- Easy to maintain
- Good accessibility of wearing parts
- Quick and simple replacement
- No special tools required .

Special products

- Corrosion resistant
- Explosion proof
- Frequency inverter driven 11
- 11 Handy chain and telescopic models
- Synchronised hoist 11
- Low headroom version





